



Compounds based on Gypsum. Gypsum plasters & binders.

The fine building materials from Krone Feine Gips.





For painters and decorators

With the first-class fillers from Krone Feine Gips make perfect coating, wallpapering and gluing a success.



Füll & Glättspachtel
Filling & smoothing compound based on gypsum

Stuckateur & Malerspachtel
Stuccoer & painter finish compound based on gypsum

Multispachtel plus
Multi jointing compound based on gypsum

Multispachtel eco
Multi jointing compound based on gypsum

High filling power. Good to sand. Modified. For indoors.

High stability. Does not crack or shrink. Modified. For indoors.

Creamy stiff consistency. Strong adhesion even in thin layers. Highly modified. For indoors.

Smooth-running, quick to apply and high-yield. Easy to sand. Highly modified. For indoors.

In solid construction ¹	Concrete, masonry made of KS/aerated concrete elements, plaster	Concrete, masonry made of KS/aerated concrete elements, plaster	On standard flat substrates and in precast concrete joint	On standard flat substrates and in precast concrete joint
In drywall construction ²	–	–	Tapeless jointing compound bases on gypsum. Also as a surface filler	Tapeless jointing compound bases on gypsum. Also as a surface filler
Surface quality ³	Q1 Q2 Q3 Q4	Q1 Q2 Q3 Q4	Q1 Q2 Q3 Q4	Q1 Q2 Q3 Q4
Consumption ⁴	0.9 kg/m ² /mm (area), approx.	0.95 kg/m ² /mm (area), approx.	0.95 kg/m ² /mm (area), approx.	0.95 kg/m ² /mm (area), approx.
Max. layer thickness ⁵	4 mm	4 mm	4 mm	4 mm
Application time	1:00 h:min, approx.	1:00 h:min, approx.	0:50 h:min, approx.	0:50 h:min, approx.
Reaction to fire	Non-combustible A1	Non-combustible A1	Non-combustible A1	Non-combustible A1
Healthy living	Eurofins GOLD	Eurofins GOLD	Eurofins GOLD	Eurofins GOLD
Package size Type of packaging	0.5 kg Carton 1.0 kg Carton 1.5 kg Bag 2.0 kg Carton 5.0 kg Bag 10.0 kg Sack 25.0 kg Sack	5.0 kg Bag 25.0 kg Sack	1.5 kg Bag 5.0 kg Bag 25.0 kg Sack	5.0 kg Bag 25.0 kg Sack

1 Application according to EN 13914-2
2 Follow the processing instructions of the plasterboard manufacturer
3 For surfaces that have to meet no (Q1), normal (Q2), high (Q3) and highest (Q4) requirements (observe national regulations)
4 Depending on the condition of substrates or the drywall construction
5 Closed ≥ 1 mm thick filler layer required

For builders

Gypsum plasters and gypsum fillers for perfect walls, ceilings, interiors: top quality from Krone Feine Gips for the professional building trade.



Indoor Air Comfort

Certified raw materials and building materials for a healthy indoor climate.



Haftputzgips plus

Bonding gypsum plaster

Haftputzgips

Bonding gypsum plaster

Primofill® original

Jointing material for gypsum plasterboards

Primofill® softpower

Jointing material for gypsum plasterboards

Profi Fugenfüller

Gypsum dual-purpose compound

Manual gypsum plaster for smoothing. Can also be applied by machine. For indoors.

Plenty of slurry for easy smoothing and smoothed surfaces. Very economical. For indoors.

The original among gypsum based compounds. Does not crack or shrink. Highly modified. For indoors.

Very high strength and easy sanding. Top water retention. Highly modified. For indoors.

Mix without lumps. Uniform consistency. Good finishing. Modified. For indoors.

On suitable standard building substrates. Also in domestic kitchens & bathrooms

On suitable standard building substrates. Also in domestic kitchens & bathrooms

On standard flat substrates and in precast concrete joint

Concrete, masonry made of KS/aerated concrete elements, plaster

–

–

–

Tapeless jointing compound bases on gypsum. Also as a surface filler

Tapeless jointing compound bases on gypsum. Also as a surface filler

Dual-purpose compound based on gypsum to be used with tape.

Q1 Q2 Q3

Q1 Q2 Q3

Q1 Q2 Q3 Q4

Q1 Q2 Q3 Q4

Q1 Q2 Q3 Q4

9.2 kg/m²/10 mm, approx.

8.0 kg/m²/10 mm, approx.

0.95 kg/m²/mm (area), approx.

0.95 kg/m²/mm (area), approx.

0.2 kg/m² (joint), approx.

10 mm on average

10 mm on average

4 mm

4 mm

4 mm

2:00 h:min, approx.

1:40 h:min, approx.

1:00 h:min, approx.

0:50 h:min, approx.

0:50 h:min, approx.

Non-combustible A1

Non-combustible A1

Non-combustible A1

Non-combustible A1

Non-combustible A1

AgBB-approved*

AgBB-approved*

Eurofins GOLD

Eurofins GOLD

Eurofins GOLD

25.0 kg | Sack

25.0 kg | Sack

5.0 kg | Bag
25.0 kg | Sack

5.0 kg | Bag
25.0 kg | Sack

5.0 kg | Bag
25.0 kg | Sack

+49 5522 9909-0

kundenservice-osterode@vg-orth.de

kronefeinegips.de | ce.kronefeinegips.de



Request products



Ansetzbinder

Adhesive based on gypsum



Elektrikergips

Gypsum binder



Betonkontakt

Bonding agent



Grundiermittel

Primer



Aufbrennsperre

Primer

For dry lining. High-yield, highly adhesive, long working time. For indoors.

Fast-setting gypsum binder. Fast hardening. For indoors.

Improves the adhesion of gypsum plasters to concrete. Ready to use. For indoors.

Very High-yield concentrate. For plaster & filler substrates. For indoors.

High-yield concentrate. For plaster & filler substrates. For indoors.

Concrete, masonry

On suitable standard building substrates

Organic bonding agent for gypsum plasters on smooth, dense, non-absorbent or slightly absorbent substrates, especially concrete (with residual moisture ≤ 3 mass-%)

For uniform absorption on highly absorbent substrates and/or substrates with uneven absorbency before the application of gypsum-based plasters and finishing products. Can be diluted with max. 5 parts water

For uniform absorption on highly absorbent substrates and/or substrates with uneven absorbency before the application of gypsum-based plasters and finishing products. Can be diluted with max. 3 parts water

5.0 kg/m² dry lining, ca.

–

0.25 – 0.30 kg/m², approx.
Yield: approx. 66 – 80 m²/20.0 kg (on concrete)

0.11 kg/m², approx.
Yield: approx. 141 m²/15.0 kg (at 1:5)

0.14 kg/m², approx.
Yield: approx. 110 m²/15.0 kg (at 1:3)

2:00 h:min, approx.

0:10 h:min, approx.

Drying time, min. 24 h

Drying time, min. 24 h

Drying time, min. 24 h

Non-combustible A1

Non-combustible A1

–

–

–

Eurofins GOLD

Eurofins GOLD

AgBB-geprüft

AgBB-geprüft

AgBB-geprüft

20.0 kg | Sack

5.0 kg | Bag
10.0 kg | Sack
25.0 kg | Sack

20.0 kg | Bucket

15.0 kg | Bucket

15.0 kg | Bucket

For arts and crafts

Perfect Moulding Building Restoration:

Gypsum binders from Krone Feine Gips meet the highest demands.



**Modellgips
Alabaster**
Alabaster modelling
gypsum

Extra selected gypsum stone. Powdery finely ground. White. For indoors.



Modellgips
Modelling gypsum

Selected gypsum stone. Very finely ground. For indoors.



**Stuckgips
Primoplast®**
Gypsum binder

Gypsum binder for art, building craft, preservation of historical monuments. For indoors.

Kreativgips
Casting Compound

Fine moulding plaster for art, hobby, leisure. For indoors.

Healthy living

Eurofins GOLD

Eurofins GOLD

Eurofins GOLD

Eurofins GOLD

Package size
Type of packaging

1.5 kg | Bag
5.0 kg | Bag
25.0 kg | Sack
40.0 kg | Sack

1.5 kg | Bag
5.0 kg | Bag
20.0 kg | Sack

1.5 kg | Bag
5.0 kg | Bag
25.0 kg | Sack
40.0 kg | Sack

0.2 | 0.3 | 0.4 | 0.5 | 0.8 kg
1.0 | 5.0 kg | all in Bag
25.0 kg | Sack
All on request

Nature & Technology

Belongs in every good project: Product quality from Krone Feine Gips for industry, crafts and the home.



Fassadenspachtel
Cementitious Mortar

White cement-based powder levelling compound. Pasty to use. Highly hardened. For interior use.



Sportplatzgips
Marking powder

For commercially available dry marking trolleys. For hard and grass pitches.



Quarzsand universal
Quartz Fine Grained

Washed, dried, sieved, classified. For inside & outside.

Package size
Type of packaging

4.0 kg | Bag
20.0 kg | Sack

25.0 kg | Sack

5.0 kg | Bag
20.0 kg | Sack



FEINE GIPS



Krone Feine Gips –

First manufacture of fine building materials from plaster

Best domestic raw materials

Gentle thermal processing

Tested building material quality and product safety

Reliable materials for painters, builders and craftsmen

For sustainable buildings and healthy interiors

VG-ORTH GmbH & Co. KG

Hüttenweg 1

37520 Osterode am Harz

Phone +49 5522 9909-0

Fax +49 5522 9909-90

kundenservice-ostrode@vg-orth.de

www.kronefeinegips.de

KFG | PÜK | EN | VGO | 03.23 | 1 | 0

Krone Feine Gips

A brand of VG-ORTH GmbH & Co. KG

